



Wide screen 6MP color diagnostic monitor for new possibilities of streamlined workflow
























l **650** i2




6MP Wide Color Display

The CCL650i2 provides a viewing area equivalent to two 3MP monitors seamlessly.



Dynamic Gamma


Color Images are automatically recognized to provide optimized contrast, brightness and gamma. No user intervention is required.



Auto Text Mode

Automatic brightness control for text data to reduce eye strain for patient lists and reporting application.

Diversified Utility



Multiple system configurations can be accommodated with two Dual link DVI and two DisplayPort interface.

Luminance Stabilizing System λ-Sentinel

Color front sensor constantly monitors and accurately stabilizes luminance on the screen to optimize image quality.

Uniformity Equalizer

Luminance and color uniformity correction system produces stable images across the screen.


DICOM Conformance Check

User friendly OSD functions include DICOM conformance check function.


Specifications

| | | CCL650i2/AR : AR Coating |
|-----------------------------|------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model Name | | CCL650i2/N : No AR Coating |
| LCD Panel | Technology | 30" color TFT IPS technology |
| | Display Area | 645.5 mm × 403.05 mm |
| | Pixel Pitch | 0.197 mm × 0.197 mm |
| | Contrast Ratio | 1000 : 1(typ.) |
| | Maximum Luminance | 800 cd/m² (typ.) 410 cd/m² · 300 cd/m² (calibrated) |
| | Viewing Angle | 170° vertical and horizontal |
| Visual Performance | Native Resolution | 3280 × 2048 |
| | Display Colors | 16.77 million colors from a palette of 68 billion colors 1.07 billion colors with DisplayPort and 10-bit viewer |
| Interface | Input Signal | DVI-D (DVI 1.0 compliant) DisplayPort (DisplayPort 1.1a compliant) |
| | Plug and Play | DDC2B compliant |
| Input Power Supply | Input Power Supply | 100 V - 240 V 50 / 60 Hz |
| | Maximum Power Consumption | 180 W (typ.) |
| Features | Calibration Control | Luminance, Gamma, Color temperature Capable of storing 3 sets of LUT (Optional Calibration kit is required) |
| | OSD Information Display | Model name, Serial No., Total operating time, Calibration settings (Operating time since last calibration, Luminance, Gamma), Current luminance, Color temperature and Ambient light, DICOM conformance |
| | USB Hub | USB Rev.2.0 compliant, Self-powered USB upstream connector (×1), USB downstream connector (×2) |
| | Other Features | Uniformity Equalizer, LED indicator, Advanced power management, Dynamic Gamma, Auto text mode, A-Sentinel, Multiple LUT, Input Select by Front SW, Self DICOM check |
| Approvals | | ANSI/AAMI ES60601-1 (2005) + A1 (2012), CAN/CSA-C22.2 No. 60601-1 (2014), CE (EN60601-1, EN60601-1-2), RCM, FCC Part15 subpart B Class B , ICES-003-B, VCCI-B, FDA510(k), J-Moss, RoHS |
| Physical Characteristics | $\begin{array}{c} \text{Dimensions} \\ (\text{W} \times \text{H} \times \text{D}) \end{array}$ | 695.6 mm × 512.1 / 573.6 mm × 243.5 mm |
| | Weight | 15.8 kg |
| | THE Stand | Tilt, Swivel |
| | Mount | VESA standard (100 mm × 200 mm, 100 mm × 100 mm) |
| | Security Slot | Anti-theft security slots (display and tilt stand) |
| Accessories | | Power cord, DVI cable × 2, DisplayPort cable × 2, USB cable, User manual, Cleaning kit* *Special AR Coating model only |

Dimensions (mm)



Interface



• "JVC" is a brand of medical and industrial monitors manufactured and sold by JVCKENWOOD Corporation. • Company names and product names are the registered trademarks of the respective companies. • Product specifications and appearance are subject to change without notice. • Colors in photographs may differ from actual colors due to the printing process. • Images on screens are simulated.



- Please read the user's manual for safe and proper use.
- •Do not expose the product to dust, moisture, steam, or oily smoke. It could cause fire, electric shock, or a failure.

Healthcare Business Division JVCKENWOOD Corporation

3-12, Moriya-cho, Kanagawa-ku, Yokohama-shi, Kanagawa, 221-0022, JAPAN

TEL: +81-45-450-1908 FAX: +81-45-450-1926 Email: MEDICAL-DISPLAY.J_JKC@jvckenwood.com JVC Healthcare Website: http://healthcare.jvc.com/ Please contact our distributor below with inquiries and orders.